



Light efficiency:


40 Lumen/Watt

Light quality:

CRI: 85.1

Color temperature:

7271 K



Product name:

MOD TW100

Test:


CW

Date:


10/11/2017

Output: 2124 lm Power consumption: 53.0 W Peak: 30493 cd


Spectral distribution




Color coordinates



Zoom color point




CRI R values



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color divition from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
7271 K	85.1	17.1	81.1	91.8	81.5	0.302	0.319	0.194	0.307	0.0003

Beam details



Beam angles

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
12.6°	23.3°	37.5°

Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
30493 cd	98.6%	97.1%

Power

Power	Power factor	Power frequency
53.0 W	0.58	60 Hz

Nominal voltage	Voltage	Current
230 V	115 V	0.801 A

Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
30434lx	7609lx	3382lx	1902lx	1217lx	845lx	621lx	476lx	376lx	304lx	252lx	211lx	180lx	155lx	135lx	119lx	105lx	94lx	84lx	76lx
2827.4fcd	706.9fcd	314.2fcd	176.7fcd	113.1fcd	78.5fcd	57.7fcd	44.2fcd	34.9fcd	28.3fcd	23.4fcd	19.6fcd	16.7fcd	14.4fcd	12.6fcd	11fcd	9.8fcd	8.7fcd	7.8fcd	7.1fcd