Light efficiency:

42 Lumen/Watt

Light quality:

CRI: 0.0

Color temperature:

0 K


Output: 1653 lm

Peak: 9075 cd

Power: 39.6 W

PF: 0.53





Beam angle 24.7°


Product name:
LP 12 Hex (Full On No UV)

Item number:
Full On No UV


Date and time:
9/12/2019 10:46:33 AM

CIE 1931
x: 0.254
y: 0.230


Spectra




Power




Color details






TM-30: 0.0



CRI: 0.0 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

CQS: 0.0



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color diviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
0 K	0.0	0.0	0.0	0.0	0.0	0.254	0.230	0.193	0.263	NaN

TM-30 details


Rf 0.0

Fidelity index Rf


Rg 0.0

Gamut index Rg


		Shifts (%)	
Hue Bin	R_f	Chroma	Hue
1	0	0%	0%
2	0	0%	0%
3	0	0%	0%
4	0	0%	0%
5	0	0%	0%
6	0	0%	0%
7	0	0%	0%
8	0	0%	0%
9	0	0%	0%
10	0	0%	0%
11	0	0%	0%
12	0	0%	0%
13	0	0%	0%
14	0	0%	0%
15	0	0%	0%
16	0	0%	0%















Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
9053lx	2263lx	1006lx	566lx	362lx	251lx	185lx	141lx	112lx	91lx	75lx	63lx	54lx	46lx	40lx	35lx	31lx	28lx	25lx	23lx
841fcd	210.3fcd	93.4fcd	52.6fcd	33.6fcd	23.4fcd	17.2fcd	13.1fcd	10.4fcd	8.4fcd	7fcd	5.8fcd	5fcd	4.3fcd	3.7fcd	3.3fcd	2.9fcd	2.6fcd	2.3fcd	2.1fcd

Intensities in 0° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
9053	9025	8990	8953	8913	8831	8618	8280	7810	7163	6444	5624	4810	4039	3327	2692	2166	1695	1351	1037
100%	100%	99%	99%	98%	98%	95%	91%	86%	79%	71%	62%	53%	45%	37%	30%	24%	19%	15%	11%

Intensities in 90° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
9053	9025	8990	8953	8913	8831	8618	8280	7810	7163	6444	5624	4810	4039	3327	2692	2166	1695	1351	1037
100%	100%	99%	99%	98%	98%	95%	91%	86%	79%	71%	62%	53%	45%	37%	30%	24%	19%	15%	11%

Intensities in 180° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
9053	9069	9074	9058	9034	8927	8768	8404	7912	7250	6481	5659	4831	4013	3262	2578	2005	1549	1164	913
100%	100%	100%	100%	100%	99%	97%	93%	87%	80%	72%	63%	53%	44%	36%	28%	22%	17%	13%	10%

Intensities in 270° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
9053	9069	9074	9058	9034	8927	8768	8404	7912	7250	6481	5659	4831	4013	3262	2578	2005	1549	1164	913
100%	100%	100%	100%	100%	99%	97%	93%	87%	80%	72%	63%	53%	44%	36%	28%	22%	17%	13%	10%


Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
24.7°	**38.6°**	**49.4°**	**100.0%**	**99.9%**

Flicker


Flicker curve (complete sampled flicker signal)



Flicker frame (frame of one flicker period)



Flicker FFT (frequency scope of flicker curve)



Flicker results:

Flicker frequency:		n/a Hz	
Flicker index:	n/a	JA8/10 40Hz	n/a %
Flicker percentage:	n/a %	JA8/10 90Hz	n/a %
SVM: (Visual flicker)	n/a	JA8/10 200Hz	n/a %
PstLM	n/a	JA8/10 400Hz	n/a %
Mp	n/a	JA8/10 1000Hz	n/a %

Flicker conditions:

Sample rate:	n/a samples/second