

# PRELIMINARY DATA ONLY



## H2O TWO

**Experience the mesmerizing simulated water effect of the ADJ H2O TWO lighting fixture. With a bright 120-Watt LED and 5 Dichroic colors, this versatile fixture is perfect for projecting onto walls, ceilings, or floors, and can be used with or without fog. Its compact design and easy installation make it ideal for creating stunning lighting displays at any event or performance.**

The H2O TWO is a stimulating lighting fixture designed to bring a dynamic water-like effect to your lighting display. With a bright 120-Watt cool white LED source and 5 Dichroic colors, this fixture creates a mesmerizing simulated water effect that can be projected onto walls, ceilings, or floors. The H2O Two can be used with or without fog and is great for mood or background lighting.

This fixture is equipped with two DMX channel modes and may be controlled via DMX, the included IR wireless remote or from the built-in programs, giving you complete control over your lighting setup. The digital DMX display with a 4-button menu makes navigation easy, while the 0-100% dimming (via DMX) manual adjustable zoom and focusing lens allow you to fine-tune the lighting to your exact specifications.

Built to last, the H2O Two features long-life LED source rating of 50,000 hours, and multi-voltage operation (AC 120-240V 50/60Hz). The fixture is fan-cooled and includes a safety loop on the rear panel, ensuring reliable and safe operation. With a power consumption of only 128W (120V) or 125W (220V), the H2O TWO can run all night without the need for a duty cycle.

## OPTICAL:

- Bright, 120W Cool White LED
- Color Temperature: 7000K
- 50,000 Hour Average LED Life

## FEATURES:

- Color Wheel with 5 Dichroic Colors Plus White
- 27° to 37° Manually Adjustable Zoom
- Manual Focus of Lens for Blurry Effects
- 0.6Hz to 7.5Hz Strobe Rate
- 3 Built-In Programs
- Primary / Secondary Mode
- Fan Cooled

## CONNECTIONS:

- Data: IP20 Indoor locking 5-pin DMX In/Out
- Power: IP20 Indoor locking power In/Out
- Safety Loop

## CONTROL:

- Control Protocol: DMX and IR Remote
- 2 DMX Modes: 4 and 9 channel modes
- Dim Modes: 6 Presets (Standard, Stage, TV, Architectural, Theatre & Stage 2)
- Dim Curves: 4 Presets (Linear, Square Law, Inv Square Law and S Curve)
- 0-100% Smooth Dimming
- Variable, Pulse & Random Strobe Modes
- Max Strobe Rate 7.5Hz. Min Strobe Rate: 0.6Hz.
- With Wired Digital Communication Network
- Display: OLED display with 4-button touch menu

## ELECTRICAL:

- 100-240V 50Hz/60Hz., Auto Sensing, Power Input
- Power Out to link multiple like units
- Max Power Consumption: 128W @120V., 125W @220V.
- Max Power Link: 8pcs @120V., 16pcs @220V.
- Fuse Protected: T5A/250V Glass Fuse (5\*20MM)

## DIMENSIONS / WEIGHT:

- Length: 12.4" (315mm)
- Width: 9.09" (231mm)
- Height: 9.21" (234mm)
- Weight: 11.02 lbs. (5 kg)



**UCIR REMOTE  
INCLUDED WITH  
FIXTURE**



## APPROVALS / RATINGS:

- CE
- cETLus (Pending)
- IP20

## WHAT'S INCLUDED:

- 1x 6ft (1.83m), 3x18AWG, Indoor Power Locking to Edison power cable (U.S.)
- 1x UC-IR (IR Remote)

Unfocus lens for Blurry Effects

