Light efficiency:

17 Lumen/Watt

Light quality:

CRI: 68.1

Color temperature:

8006 K

Output: 3060 lm

Peak: 49783 cd

Power: 185.4 W

PF: 1.0



Beam angle 14.8°

Product name:
Vizi Xtreme (Full On,8000K)

Item number:

Date and time:
8/26/2026 2:15:23 PM

CIE 1931
x: 0.297
y: 0.299

Spectra



Power



Color details



CIE 1931



CIE 1931 ZOOM

TM-30: 75.1



CRI: 68.1 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
74.5	93.5	56.7	53.8	79.6	90.1	64.4	31.9	-68.7	82.0	46.7	73.5	83.8	74.5	58.3

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
61.2	77.7	85.8	87.1	78.8	74.4	78.3	80.8	88.0	87.8	60.4	60.5	61.5	64.7	53.4	68.1

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
79.8	87.5	77.7	93.4	83.5	81.2	94.8	82.1	72.9	85.7	96.7	84.2	77.6	88.8	87.3

CQS: 83.5



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color diviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
8006 K	68.1	-68.7	75.1	118.5	83.5	0.297	0.299	0.199	0.299	-0.0046

TM-30 details

Rf 75.1

Fidelity index Rf

Rg 118.5

Gamut index Rg

		Shifts (%)	
Hue Bin	R_f	Chroma	Hue
1	61	21%	-3%
2	78	9%	-8%
3	86	7%	-4%
4	87	2%	8%
5	79	7%	9%
6	74	15%	8%
7	78	14%	-3%
8	81	9%	-6%
9	88	-3%	0%
10	88	-6%	5%
11	60	-4%	20%
12	61	-6%	30%
13	62	5%	32%
14	65	10%	20%
15	53	33%	29%
16	68	17%	0%













Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
49783lx	12446lx	5531lx	3111lx	1991lx	1383lx	1016lx	778lx	615lx	498lx	411lx	346lx	295lx	254lx	221lx	194lx	172lx	154lx	138lx	124lx
4625fcd	1156.2fcd	513.9fcd	289.1fcd	185fcd	128.5fcd	94.4fcd	72.3fcd	57.1fcd	46.2fcd	38.2fcd	32.1fcd	27.4fcd	23.6fcd	20.6fcd	18.1fcd	16fcd	14.3fcd	12.8fcd	11.6fcd

Intensities in 0° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
49.8k	49.2k	47.7k	45.6k	42.7k	38.7k	34.1k	27.7k	19.9k	11.7k	5.1k	1.6k	0.3k	0.1k	0.1k	0.1k	0.0k	0.0k	0.0k	0.0k
100%	99%	96%	92%	86%	78%	68%	56%	40%	23%	10%	3%	1%	0%	0%	0%	0%	0%	0%	0%

Intensities in 90° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
49.8k	49.2k	47.7k	45.6k	42.7k	38.7k	34.1k	27.7k	19.9k	11.7k	5.1k	1.6k	0.3k	0.1k	0.1k	0.1k	0.0k	0.0k	0.0k	0.0k
100%	99%	96%	92%	86%	78%	68%	56%	40%	23%	10%	3%	1%	0%	0%	0%	0%	0%	0%	0%

Intensities in 180° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
49.8k	49.2k	47.7k	45.6k	42.7k	38.7k	34.1k	27.7k	19.9k	11.7k	5.1k	1.6k	0.3k	0.1k	0.1k	0.1k	0.0k	0.0k	0.0k	0.0k
100%	99%	96%	92%	86%	78%	68%	56%	40%	23%	10%	3%	1%	0%	0%	0%	0%	0%	0%	0%

Intensities in 270° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
49.8k	49.2k	47.7k	45.6k	42.7k	38.7k	34.1k	27.7k	19.9k	11.7k	5.1k	1.6k	0.3k	0.1k	0.1k	0.1k	0.0k	0.0k	0.0k	0.0k
100%	99%	96%	92%	86%	78%	68%	56%	40%	23%	10%	3%	1%	0%	0%	0%	0%	0%	0%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
14.8°	**20.1°**	**22.4°**	**90.5%**	**88.7%**

Flicker

Flicker curve (complete sampled flicker signal)

Flicker frame (frame of one flicker period)



Flicker FFT (frequency scope of flicker curve)



Flicker results:

Flicker frequency:		1176.47 Hz	
Flicker index:	0.06	JA8/10 40Hz	0.18 %
Flicker percentage:	30.18 %	JA8/10 90Hz	0.2 %
SVM: (Visual flicker)	0.19	JA8/10 200Hz	0.2 %
PstLM	0	JA8/10 400Hz	0.35 %
Mp	0.08	JA8/10 1000Hz	2.94 %

Flicker conditions:

Sample rate:	20000 samples/second