

SABER SPOT UV

Saber Spot UV is a compact UV LED pinspot fixture featuring a 15-Watt UV LED source, a tight 7-degree beam angle, and interchangeable 45° frost filter. It is DMX and RDM compliant, offers smooth 0–100% electronic dimming, and includes a scissor yoke for flexible mounting or floor use.

The Saber Spot UV is fully DMX and RDM compliant and offers flexible control with 1- or 2-channel DMX modes, along with IR wireless remote operation. A 4-button digital display provides intuitive menu navigation, while smooth 0–100% electronic dimming allows for precise intensity control.

Built for versatility, the Saber Spot UV features a durable scissor yoke for hanging or ground placement. It includes locking power input and pass-through connections, along with 5-pin DMX input/output pigtails and wired digital communication network support. With efficient power consumption and the ability to link up to 57 units at 120V or 95 units at 230V, it is ideal for scalable installations.

Housed in a sleek black enclosure, the Saber Spot UV measures 6.69" x 5.31" x 8.46" and weighs just 3.2 lbs., making it easy to transport and install. It is CE and cETLus approved and carries an IP20 rating for indoor use.

Included with the Saber Spot UV are a 1.83m indoor locking power cord, one interchangeable 45-degree frost filter lens, and a metal clip ring for secure installation. Optional accessories include PLC Series indoor locking power link cables and the UC IR remote controller.

SABER SPOT UV

OPTICAL:
- Light Source: 15-Watt, UV LED
- LED Life Expectancy: 30,000 Hrs
- Beam Angle: 7°
- Includes 45-degree interchangeable frost filter lens
- LED Refresh Rate: 3.6KHz

TECHNICAL FEATURES:
- DMX and RDM Compliant
- 4-button Digital Display for easy navigation
- Electronic Dimming 0 – 100%
- Includes a scissor yoke to be hung, or set on the ground

CONNECTIONS:
- Power Input: Indoor locking power
- Power Pass through: Indoor locking power
- Control: 5-pin DMX In/Out pigtails
- With Wired Digital Communication Network

CONTROL:
- 2 DMX Channel Modes: 1 & 2 CH
- RDM Compliant
- IR (IR Remote Control)

ELECTRICAL:
- Input Voltage: 100-240V 50Hz/60Hz (Auto Sensing)
- Power draw 120V 60Hz: 16.7W, 0.243 Amps
- Power draw 230V 50Hz: 16.7W, 0.147 Amps
- Power Output Current: 1.2A (14W)
- Power Linking: 57pcs @120V, 95pcs @230V

PHYSICAL:
- Dimensions (LxWxH): 6.69" x 5.31" x 8.46" (170 x 135 x 215mm)
- Weight: 3.2 lbs / 1.45 kg.
- Black Housing





SABER SPOT UV

APPROVALS / RATINGS:
- CE
- cETLus Approval (Pending)
- IP20

WHAT'S INCLUDED:
- 1.83m Indoor locking power cord
- 45-degree frost filter
- Metal clip ring for frost filter

OPTIONAL ACCESSORIES:
- PLC 3, PLC 6, PLC 10 (Indoor locking power link cables)







