



Light efficiency:


28 Lumen/Watt

Light quality:

CRI: 0.0

Color temperature:

0 K



Product name:

7PZ IP

Test:


Zoom 50% Green

Date:


4/21/2017

Output: 1224 lm Power consumption: 44.4 W Peak: 12588 cd


Spectral distribution




Color coordinates



Zoom color point




CRI R values



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color divition from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
0 K	0.0	0.0	0.0	0.0	0.0	0.151	0.709	0.054	0.380	n/a

Beam details



Beam angles

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
14.3°	25.7°	34.6°

Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
12588 cd	1.0%	1.0%

Power

Power	Power factor	Power frequency
44.4 W	0.97	60 Hz

Nominal voltage	Voltage	Current
230 V	118 V	0.389 A

Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
9980lx	2495lx	1109lx	624lx	399lx	277lx	204lx	156lx	123lx	100lx	82lx	69lx	59lx	51lx	44lx	39lx	35lx	31lx	28lx	25lx
927.2fcd	231.8fcd	103fcd	58fcd	37.1fcd	25.8fcd	18.9fcd	14.5fcd	11.4fcd	9.3fcd	7.7fcd	6.4fcd	5.5fcd	4.7fcd	4.1fcd	3.6fcd	3.2fcd	2.9fcd	2.6fcd	2.3fcd